

Product sheet

Soundtile tactile pathway, type GLB-02 en GLB-07



Product description

Sound tile for use as tactile pathway element in public areas or in public transport.

Product code

GLB-02, for use in cement bed/concrete (element).

GLB-07, for use in sand bed.

Field of application

Outdoors and (partly) indoors.

Material

Aluminium, anodised and sandblasted.

Tile is topped up with concrete; by using a plastic blister a hollow chamber is created which produces a sound when in contact with a cane or shoe.

Colour

Silver/white, anthracite, gold/yellow; diffusely reflective for high attention value with residual vision.

Dimensions

300 x 300 x 20 mm (GLB-02)

300 x 300 x 65 mm (GLB-07)

Profile

5 x parallel Strips, centre-to-centre dimension 60 mm. Dimensions of Strips: 250 x 15 x 5 mm.

Required number of sound tiles

May be used as a single or double row; per linear metre, 3.33 or 6.66 are required.

Installation in a sand bed

Arrange tiles on a bed of sand which is compacted and laid under the correct profile. To keep the sound box intact, do not tap with a hammer or vibrate.

Installation in a cement bed/concrete (element)

Mill or create a recess using polystyrene (or equivalent) having the dimensions of the warning markings + 5 mm L x W x H. Affix the sound tiles with adhesive.

Applicable guideline

Product dimensions and profile can be fully adjusted to national standards or requirements.

Contact data

TG Lining bv
De Droogmakerij 77
1851 LX Heiloo (NL)
The Netherlands
+31 (0)72 5070153
info@tglining.com
www.tglining.com