

## Product sheet

### Tactile guiding ridges train, prefabricated

#### Product description

Epoxy guiding strips for the benefit of people with visual impairments.

#### Product code

TGGL-BRPR.

#### Field of application

On (concrete) paving bricks, concrete tiles and floor tiles.

#### Substrate conditions

For the sake of optimal adhesion, the substrate can be degreased and/or roughened, only on those spots where strips/ridges are to be installed.

#### Chemical composition

Two-component synthetic resin.  
Component A, modified epoxy resin.  
Component B, hardener.

#### Standard shape and dimensions

Strips length: 150/250/350 mm  
Strip width: 30 mm  
Strips height: 1 to 4.5 mm above the finished floor  
Shape: rectangular, rounded or triangular cross-section

Variations on shape and dimensions possible.

#### Standard colours

White (RAL 9001), black (RAL 9011).

Other RAL colours available on request.

#### Processing

At TG Lining plant, (paving) material to be supplied in advance by the customer.

#### Cleaning advice

Clean manually or with a scrubbing machine (preferably non-rotating). If using chemical cleaning solutions, first cleaning 5 days after application.

#### Applicable guideline

Product dimensions and profile can be fully adjusted to national standards or requirements.

Contact data

TG Lining bv  
De Droogmakerij 77  
1851 LX Heiloo  
The Netherlands  
+31 (0)72 5070153  
[info@tglining.com](mailto:info@tglining.com)  
[www.tglining.com](http://www.tglining.com)

