

Product sheet

Anti-slip markings, installed in situ

Product description

Epoxy markers as anti-slip marking.

Product code

TGGL-AS.

Field of application

Indoors and outdoors on all types of solid substrates other than blue ashlar stone and tropical hardwoods.

Substrate conditions

Substrate should be dry and swept clean. For the sake of optimal adhesion, the substrate can be degreased and/or roughened, only on those spots where markings are to be installed.

Chemical composition

Two-component synthetic resin.
Component A, modified epoxy resin.
Component B, hardener.

Standard shape and dimensions

Base structure:	5 parallel Strips
Centre-to-centre dimension:	60 mm
Working path width:	300 mm
Strips length:	150/250/350 mm
Strips width:	10 mm
Strips height:	approx. 0.5 mm above the finished floor
Intermediate distance:	50 mm in longitudinal direction to drain dirt and water
Shape:	rectangular

Variations on shape and dimensions possible.

Standard colours

White (RAL 9001), black (RAL 9011).

Other RAL colours available on request.

Processing

In dry weather and at a minimum temperature of 10°C.

Curing time

Can be walked on after approximately 12 hours at a processing temperature of 10°C or higher.
No post-processing is necessary.

Cleaning advice

Clean manually or with a scrubbing machine (preferably non-rotating). If using chemical cleaning solutions, first cleaning 5 days after application.

Contact data

TG Lining bv
De Droogmakerij 77
1851 LX Heiloo
The Netherlands
+31 (0)72 5070153
info@tglining.com
www.tglining.com

