

## Product sheet

### Tactile guiding ridges, prefabricated

#### Product description

Epoxy guiding strips for the benefit of people with visual impairments.

#### Product code

TGGL-SPR.

#### Field of application

On (concrete) sand-faced paving bricks, concrete tiles and floor tiles.

#### Substrate conditions

For the sake of optimal adhesion, the substrate can be degreased and/or roughened, only on those spots where strips/ridges are to be installed.

#### Chemical composition

Two-component synthetic resin.  
Component A, modified epoxy resin.  
Component B, hardener.

#### Standard shape and dimensions

Structure:	10 parallel Stripss
Centre-to-centre dimension:	60 mm
Working path width:	600 mm
Strips length:	150/250/350 mm
Strips width:	10 mm
Strips height:	1 to 4.5 mm above the finished floor
Intermediate distance:	50 mm in longitudinal direction to drain dirt and water
Shape:	rectangular, rounded or triangular cross-section

Variations of shape and dimensions possible.

#### Standard colours

White (RAL 9001), black (RAL 9011).

Other RAL colours available on request.

#### Processing

At TG Lining plant, (paving) material to be supplied in advance by the customer.

#### Cleaning advice

Clean manually or with a scrubbing machine (preferably non-rotating). If using chemical cleaning solutions, first cleaning 5 days after application.

Applicable guideline

Product dimensions and profile can be fully adjusted to national standards or requirements.

Contact data

TG Lining bv  
De Droogmakerij 77  
1851 LX Heiloo (NL)  
+31 (0)72 5070153  
[info@tglining.com](mailto:info@tglining.com)  
[www.tglining.com](http://www.tglining.com)

